



अतिरिक्त जानकारी Addendum -01

यू.आर.एस.सी./सार्वजनिक निविदा सूचना सं / URSC/GLOBAL TENDER NOTICE NO.E-04/26-27 16.07.2026

विषय: निविदा पृष्ठताछ में परिशिष्ट जारी करने की स्वीकृति - संबंधित।

Sub: Approval to issue Addendum to Tender Enquiry - Reg

संदर्भ/Ref: URSC/GLOBAL TENDER NOTICE NO.E-04/26-27 03.07.2026

URSC/PR/ IS2026-00-0512-01 - 03.07.2026

यह उपरोक्त वैश्विक निविदा - सार्वजनिक निविदा - के संबंध में है, जिसे 02.07.2026 को दो भागों में जारी किया गया था। निविदा संबंधी स्पष्टीकरण के लिए अंतिम तिथि 10.07.2026 है, और निविदा जमा करने की अंतिम तिथि 31.07.2026 है।

This has reference to the above Global Tender - Public Tender - Two part floated on 03.07.2026 with bid clarification date up to 10.07.2026 and bid submission date up to 31.07.2026.

यह सूचित किया जाता है कि सभी संभावित बोलीदाताओं को यह जानकारी दी जाती है कि निम्नलिखित दस्तावेज़ उपरोक्त निविदा के साथ संलग्न किया गया है और यह निविदा दस्तावेजों का एक अभिन्न अंग होगा।

This is to inform all prospective bidders that the following document is hereby attached to the above-mentioned tender and shall form an integral part of the tender documents:

सीडीआर31 और सीडीआर32 कैपेसिटर से संबंधित खरीद विनिर्देशों/अनुपालन मैट्रिक्स।
Procurement specifications / Compliance Matrix pertaining to “CDR31 & CDR32 Capacitors”

निवेदकों से अनुरोध है कि वे उपरोक्त बातों पर ध्यान दें और अपनी बोलियाँ तैयार करते और जमा करते समय संलग्न दस्तावेज़ पर विचार करें। Bidders are requested to take note of the above and consider the attached document while preparing and submitting their bids.

निविदा के अन्य सभी नियम और शर्तें अपरिवर्तित रहेंगी All other terms and conditions of the tender remain unchanged.

क्र.सं. Sl. No.	कार्यक्रम Events	के स्थान पर In place of	ऐसा पढ़ा जाए To be read as
1	बोली स्पष्टीकरण दिनांक Bid clarification date	10.07.2026; 16:00 hrs	23.07.2026 ; 16:00 hrs
2	बोली प्रस्तुतीकरण दिनांक Bid submission date	31.07.2025; 14:00 hrs	31.07.2026 ; 14:00 hrs
3	बोली खोलने की दिनांक Bid opening date	31.07.2026; 14:30 hrs	31.07.2026 ; 14:30 hrs

Sd/-

व. प्रधान, क्रय व भंडार / Sr. Head, Purchase & Stores

PROCUREMENT SPECIFICATIONS FOR CERAMIC CHIP CAPACITOR CDR

SINO	Specification	Compliance/ Remarks
A	Quality Requirements:	
A1	Qualified to Generic Specification: MIL-PRF-55681	
A2	Failure rate level: 'S'	
B	Component Specification:	
B1	Style: CDR	
B2	Value/Tolerance/Temperature Coefficient/Voltage : As per Table-1	
B3	End termination: 'U' (Base metallization - barrier metal solder coated.)	
C	Test Requirements:	
C1	The components shall have undergone Group 'A' tests as per MIL-PRF-55681	
D	Datapack Requirements:	
D1	Certificate of Conformance from the manufacturer.	
E	Other requirements:	
E1	The name of the manufacturer shall be specified as part of the offer.	
E2	The devices shall be drawn from lots manufactured less than 2 years of the date of shipment.	
E3	No pure tin shall be used in the fabrication/assembly of the component.	
E4	Latest data sheet of the quoted item shall be sent along with the offer.	
E5	Only OEM/OEM authorized suppliers for the above space grade components will be considered. In case of authorized supplier, necessary certificate from the OEM shall be enclosed along with the offer.	
E6	Capacitors shall be supplied in a packing that bears a label giving details such as a. Part number b. Value c. Tolerance d. End termination e. Failure Rate f. Manufacturer etc.	
E7	Packing material shall be ESD compliant.	
E8	Report to URSC all NCR/DCN during procurement/testing.	

Note: Please provide compliance/remarks in the column provided.

TABLE 1

Sl. No.	SIZE	VALUE	TOL(+/-)	TC	VOLTAGE
1	CDR31	10 PF	+/-1%	30 PPM	100V
2	CDR31	15 PF	+/-1%	30 PPM	100V
3	CDR31	18 PF	+/-1%	30 PPM	100V
4	CDR31	22 PF	+/-1%	30 PPM	100V
5	CDR31	47 PF	+/-1%	30 PPM	100V
6	CDR31	100 PF	+/-1%	30 PPM	100V
7	CDR31	150 PF	+/-1%	30 PPM	100V
8	CDR31	200 PF	+/-1%	30 PPM	100V
9	CDR31	220 PF	+/-1%	30 PPM	100V
10	CDR31	270 PF	+/-1%	30 PPM	100V
11	CDR31	330 PF	+/-1%	30 PPM	100V
12	CDR31	390 PF	+/-1%	30 PPM	100V
13	CDR31	470 PF	+/-1%	30 PPM	100V
14	CDR31	560 PF	+/-10%	TC+15%-25%	100V
15	CDR31	680 PF	+/-10%	TC+15%-25%	100V
16	CDR31	1 KPF	+/-10%	TC+15%-25%	100V
17	CDR31	2.2 KPF	+/-10%	TC+15%-25%	100V
18	CDR31	3.9 KPF	+/-10%	TC+15%-25%	100V
19	CDR31	4.7 KPF	+/-10%	TC+15%-25%	100V
20	CDR31	5.6 KPF	+/-10%	TC+15%-25%	50V
21	CDR31	8.2 KPF	+/-10%	TC+15%-25%	50V
22	CDR31	10 KPF	+/-10%	TC+15%-25%	50V
23	CDR31	15 KPF	+/-10%	TC+15%-25%	50V
24	CDR31	18 KPF	+/-10%	TC+15%-25%	50V
25	CDR32	10 PF	+/-1%	30 PPM	100V
26	CDR32	100 PF	+/-1%	30 PPM	100V
27	CDR32	330 PF	+/-1%	30 PPM	100V
28	CDR32	470 PF	+/-1%	30 PPM	100V
29	CDR32	560 PF	+/-5%	30 PPM	100V
30	CDR32	680 PF	+/-1%	30 PPM	100V

Sl. No.	SIZE	VALUE	TOL(+/-)	TC	VOLTAGE
31	CDR32	820 PF	+/-1%	30 PPM	100V
32	CDR32	1 KPF	+/-1%	30 PPM	100V
33	CDR32	1.1 KPF	+/-10%	30 PPM	50V
34	CDR32	1.5 KPF	+/-5%	30 PPM	50V
35	CDR32	1.8 KPF	+/-5%	30 PPM	50V
36	CDR32	2.2 KPF	+/-1%	30 PPM	50V
37	CDR32	4.7 KPF	+/-10%	TC+15%-25%	100V
38	CDR32	5.6 KPF	+/-10%	TC+15%-25%	100V
39	CDR32	6.8 KPF	+/-10%	TC+15%-25%	100V
40	CDR32	8.2 KPF	+/-10%	TC+15%-25%	100V
41	CDR32	10 KPF	+/-10%	TC+15%-25%	100V
42	CDR32	15 KPF	+/-10%	TC+15%-25%	100V
43	CDR32	27 KPF	+/-10%	TC+15%-25%	50V
44	CDR32	39 KPF	+/-10%	TC+15%-25%	50V